

# Eco Current Profiler



Shallow-water current profiles in a groundbreaking new package. Appropriate for first-time ADCP users, small budgets or educational use.

The Eco current profiler is the first ADCP right-sized and designed specifically for shallow-water measurements. It allows you to measure water velocities *in situ*, through the water column using the same acoustic Doppler technology as other Nortek instruments, but in a more affordable and easy-to-use package. Simple buoy and bottom-mount solutions are available and designed to fit Eco off-the-shelf. Eco is portable enough to be put in the water from a paddle board or kayak by one person. While the Eco does not feature many of the more complex capabilities of other Nortek instruments, such as wave measurements, turbulence estimation, or echosounder data, Eco *does* present a host of new, unique capabilities.

# Eco Current Profiler



## Highlights

- ✓ Build your instant proposal in the Eco Webshop to submit to purchasing or buy online
- ✓ Self-configuring data collection in various depths and water types
- ✓ Seamless current profiles from 30cm to 20m from the instrument
- ✓ Weighs only 1 kg in air and is only 13 cm tall
- ✓ Built-in battery and inductive battery charger. No cables or connectors!
- ✓ Integrated deployment and recovery system available
- ✓ Automated data processing to ensure quality data reports with no prior ADCP experience
- ✓ Built-in GNSS, temperature, pressure and tilt sensors

## Applications

- ✓ Estuarine studies
- ✓ Sediment transport studies
- ✓ Studies of tidal currents
- ✓ Coral reef studies
- ✓ Educational use

## Technical specifications

### → Water velocity measurements

Maximum profiling range	20 m
Cell size	Self-configured (profiling range 0.3-20 m)
Minimum blanking	0.1 m
Maximum number of cells	3
Accuracy	±1% of measured value ±0.5 cm/s
Maximum sampling rate (output)	2, 4, 5, 6, 8 10, 20, 30 or 60 minutes
Velocity range (horizontal)	±5 m/s

### → Echo intensity (along slanted beams)

Sampling	N/A
Transducer acoustic frequency	1 MHz
Number of beams	3
Beam width	3.4°

### → Wave Measurement option

Type	N/A
------	-----

### → Sensors

Temperature	Thermistor in head
Temp. range	-4 to +40 °C
Temp. accuracy/resolution	0.1 °C/0.01 °C
Temp. time response	2 min
Compass	Solid-state magnetometer
Accuracy/resolution	3° for tilt < 30°/0.01°
Tilt	Solid-state accelerometer
Accuracy/resolution	0.2° for tilt < 30°/0.01°
Maximum tilt	30°
Up or Down	N/A
Pressure	Piezoresistive
Range	50 m
Accuracy/precision	0.5% FS / 0.005% of full scale
Position	embedded GNSS receiver
Accuracy	3 m

### → Analog inputs

No. of channels	N/A
-----------------	-----

### → Data recording

# Eco Current Profiler



Capacity	16 GB (>5 yrs back-to-back monthly deployments without formatting)
→ Real-time clock	
Accuracy	±2 min/year
→ Data communications	
I/O	Bluetooth Low Energy (BLE)
User control	Smart device and PC App with secure cloud storage Eco account
→ Connectors	
Bulkhead	None
Cable	None
→ Software	
Functions	Deployment planning, instrument configuration, data retrieval, secure cloud storage, automatic data processing, automatic report generation, deployment position mapping with embedded GNSS.
→ Power	
DC input	N/A
→ Batteries	
Battery capacity	70 Wh rechargeable smart Li-ion charged by induction
→ Environmental	
Operating temperature	-5 to +40 °C
Storage temperature	-20 to +60 °C
Shock and vibration	IEC 60068
EMC approval	EN301489, EN 61326, EN61000
Depth rating (Eco)	50 m
Depth rating (Release)	60 m
→ Materials	
Standard model	POM
→ Dimensions	
Maximum diameter	85 mm
Maximum length	130 mm
→ Weight	
Weight in air	1.02 kg
Weight in water	0.28 kg